

TYPICAL LAY-IN PANEL CEILING PLAN
N.T.S.
1 / A1



NOTE
1. CONNECT RUNNERS TO NO MORE THAN TWO ADJACENT WALLS PROVIDE SLIP-JOINT WITH 1/2" SEPARATION AT ALL OTHER WALLS.
2. FOR LIGHT FIXTURE SEE 3/A1 WHERE OCCURS

SUSPENDED ACOUS. CLG. LATERAL BRACING (CROSS SECTION)
N.T.S.
2 / A1



EXTR	MAX. LENGTH
3/4"	5'-0"
1"	6'-0"
1 1/4"	8'-0"

OR UP TO 6' 8" USE: 2 1/2" X 1 1/4" 20 GA STEEL STUD ATTACHED TO RUNNER WITH 2-#8 SELF-DRILLING PAN HEAD SCREWS AND 2-#8 SELF-DRILLING PAN HEAD SCREWS AND 3/16" DIAMETER POWDER DRIVEN PIN OR 2-#10 SCREWS

SUSPENDED ACOUSTICAL CEILING LATERAL BRACING
N.T.S.
3 / A1



NOTE
1. FOR WEIGHT LESS THAN 56 LBS (BALL CONTACT ARCHITECT IF FIXTURE WEIGHS MORE THAN 56 LBS.

LIGHTING OR MECH. FIXTURE
N.T.S.
4 / A1



HANGER ATTACHMENT
N.T.S.
5 / A1



BRACE TO STRUCTURE (U)	BRACE SIZE
UP TO 8'-0"	1 5/8" x 1-1/2" x 20 GA SL STUD
8'-0" TO 9'-4"	1 5/8" x 1-1/2" x 20 GA SL STUD

PARTITION BRACE
3/4" = 1'-0"
6 / A1

REVISIONS / ISSUES			
NO.	DATE	BY	APPR.
NO.	DATE	BY	APPR.
NO.	DATE	BY	APPR.
NO.	DATE	BY	APPR.

FILE: J:\0600\0600\A10-3
SCALE:
DESIGNED BY:
DRAWN BY:
CHECKED BY:
APPROVED BY:
DATE: 2/20/1997
PROJECT NO: V0600

CEILING SEISMIC RESTRAINT
SHEET NO. A10.3
REV. NO. 1

J:\0600\0600\A10-3 Lewis Ed Centre, VZM Corporation
01-08-98 12:00:26 XRef Files